

tesa® 64285 PV10

Product Information

Tensilised polypropylene tape

Product Description

tesa® 64285 is a tensilised polypropylene tape with a natural rubber adhesive.

tesa® 64285 exhibits good tensile strength with low elongation at the same time.

The product is especially recommended for handylift applications.

Product Features

- · high tensile strength
- low elongation

Application Fields

- · Prematerial for handylift
- · Palletising, adhering or bundling are also possible

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	MOPP	•	Total thickness	72 μm
•	Type of adhesive	synthetic rubber	•	Color	transparent

Properties/Performance Values

•	Elongation at break	35 %	•	No discoloration	yes
•	Tensile strength	180 N/cm	•	Residue-free removability	yes

Adhesion to Values

• Steel 6 N/cm





tesa® 64285 PV10

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

