



# tesa<sup>®</sup> 4329 PV1



## Product Information

Flexible masking tape for spray painting

## Product Description

tesa<sup>®</sup> 4329 is a flexible masking tape based on a fine crepe paper backing and a natural rubber adhesive. It is suitable for lightly duty spray painting and general purpose masking applications. The natural rubber adhesive system features good adhesion and tack to multiple surfaces. The excellent adherence of fillers or paints (water- or solvent-based) to the reverse side of the tape prevents any kind of paint flaking. It has a temperature resistance up to 70 °C for subsequent oven-drying.

## Sustainable Aspects

57% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

## Product Features

- Good flexibility for masking of curves
- Good adhesion tack to various surfaces
- Paints and fillers adhere to the reverse side
- Temperature resistance up to 70 °C

## Application Fields

- Suited for painting and lacquering work
- Masking during spray painting with subsequent oven drying up to 70 °C / 1h

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                       |  |        |
|--------------------|-----------------------|--|--------|
| • Backing          | slightly-creped paper | • Total sustainable product excl. liners by weight (acc. EN 16785) | 57 %   |
| • Type of adhesive | natural rubber        | • Total thickness  | 125 µm |

## Properties/Performance Values

- |                       |         |                                   |           |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 10 %    | • Hand tearability                | very good |
| • Tensile strength    | 33 N/cm | • Temperature resistance (60 min) | 80 °C     |
| • Easy to remove      | yes     |                                   |           |

For latest information on this product please visit <http://l.tesa.com/?ip=04329>



# tesa<sup>®</sup> 4329 PV1

## Product Information

### Adhesion to Values

- Steel 2.8 N/cm

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04329>