

# tesa® Professional 4169 Permanent Marking Tape Premium

**Product Information** 

Premium floor marking tape

## **Product Description**

tesa<sup>®</sup> 4169 is an extremely robust high-performance adhesive tape for permanent floor markings. The abrasion-resistant, robust and resilient floor-marking tape comprises a soft PVC substrate with an acrylate adhesive mass. It can also be used on sensitive or rough surfaces and, thanks to the high degree of flexibility in the substrate, is also suitable for adhesion to corners. tesa<sup>®</sup> 4169 is available in black, green, white, blue, red, yellow and yellow/black; the colour combinations correspond to legally prescribed safety guidelines. Depending on its colour, the floor-marking tape can be explicitly used as a warning tape.

## **Application Fields**

- Indoor and outdoor applications
- Permanent, high-traffic floor markings
- Marking of working areas in workshops
- Mark out courts in sports halls

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

# **Product Construction**

•	Backing	soft PVC	•	Total thickness	180 µm
٠	Type of adhesive	acrylic			

#### **Properties/Performance Values**

•	Elongation at break Tensile strength Abrasion resistance Ageing resistance (UV) Easy to remove Easy to write on	200 % 30 N/cm very good good no	•	Fluorescent Fogging Hand tearability Humidity resistance Suitable for rough surfaces Water resistance	no good good good good
•	Easy to write on	no	•	Water resistance	good

## Adhesion to Values

Steel

1.8 N/cm



# tesa® Professional 4169 Permanent Marking Tape Premium

**Product Information** 

## **Additional Information**

The plain colours of tesa® 4169 PV3 are according to the RAL colour scheme.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 26/08/24 – en-NG