



# tesa® 60670

## Product Information



Robust aluminum tape - 75µ foil

### Product Description

tesa® 60670 is a robust aluminum tape based on a 75 µm (3 mil) aluminum foil and a transparent acrylic adhesive.

### Product Features

- Mechanical stable
- \* Easy to unwind
- \* Suitable for permanent applications
- \* Barrier against moisture, gases and vapors
- \* Electrically and thermally conductive
- \* Aging resistant
- \* Heat and light reflective
- \* Flame retardant according to DIN 4102, class B1
- \* Flame retardant according to the requirements in UL 510A
- \* Meets requirements of UL723

### Application Fields

- Repairs on trucks and trailers
- Joining and sealing of thermal insulation, ducts and pipes
- To make substrates electrically and thermally conductive
- To reflect heat radiation

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                     |          |
|--------------------|----------------|---------------------|----------|
| • Backing          | aluminium foil | • Total thickness   | 125 µm   |
| • Type of adhesive | acrylic        | • Thickness of tape | _NULL µm |
| • Type of liner    | none           |                     |          |

For latest information on this product please visit <http://l.tesa.com/?ip=60670>



# tesa<sup>®</sup> 60670

## Product Information

### Properties/Performance Values

- |                               |            |                               |           |
|-------------------------------|------------|-------------------------------|-----------|
| • Elongation at break         | 8 %        | • Hand tearability            | very good |
| • Tensile strength            | 60 N/cm    | • Operation temperature from  | -40 °C    |
| • Backing appearance (visual) | reflective | • Operation temperature up to | 160 °C    |
| • Easy to remove              | no         |                               |           |

### Adhesion to Values

- |                   |          |                 |         |
|-------------------|----------|-----------------|---------|
| • Glass (initial) | 10 N/cm  | • PVC (initial) | 7 N/cm  |
| • PE (initial)    | 5.5 N/cm | • Steel         | 10 N/cm |

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60670>