



tesa[®] 60462 PCR duct tape

Product Information

General purpose duct tape

Deskripsi Produk

tesa[®] 4615 is a utility duct grade for general purpose applications. It consists of a 27 mesh woven fabric laminated on a colored PE film. The product is coated with a synthetic rubber adhesive with solvent-free technology.

Sustainable Aspects

- 67% of the backing is made from post-consumer recycled plastics, which accounts for 30 % of the total product
- Each roll in 50mm:50m replaces 146 gram virgin plastic with post-consumer recycle



Product Features

- Bonds instantly with excellent adhesion on a variety of materials, including rough surfaces
- Unwinding is effortless and tears easily by hand
- Water repellent and extremely durable

Penerapan

The product can be used for a variety of basic applications such as

- Holding protective layers e.g. plastic films and paper sheets
- Fastening and bundling of wires, cables and loose objects
- Sealing, marking and masking even on slightly rough surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|------------------------------------|--------------------|---|--------|
| • Backing | PE laminated cloth | • Total post-consumer recycled content excl. Liners | 30 % |
| • Berbasis Bio (konten karbon-bio) | 67 % | • Total thickness | 215 µm |
| • Type of adhesive | synthetic rubber | • Thickness of tape | 215 µm |



tesa[®] 60462 PCR duct tape

Product Information

Properti / Nilai Kinerja

• Elongation at break	16 %	• Lowest application temperature	5 °C
• Tensile strength	40 N/cm	• Mesh	27 threads/inch ²
• Abrasion resistance	very good	• Suhu operasi sampai	60 °C
• Hand tearability	good	• Tack	very good
• Humidity resistance	good	• Water resistance	very good

Adhesi pada Nilai

• Backing	5 N/cm	• Steel	8 N/cm
-----------	--------	---------	--------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60462>