




# tesa<sup>®</sup> 55576

## Product Information



1200 µm double sided PE foam tape

### Deskripsi Produk

tesa<sup>®</sup> 55576 is a double sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive.

### Product Features

tesa<sup>®</sup> 55576 is a double sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive.

### Penerapan

- Trims & Profiles Mounting
- POS Signs & Advertising Material Mounting
- Mirror Pre-Mounting
- Temporary Mounting
- Gap Filling

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Konstruksi Produk

- |                 |                 |                   |         |
|-----------------|-----------------|-------------------|---------|
| • Penyangga     | PE foam         | • Ketebalan total | 1200 µm |
| • Jenis perekat | acrylic         | • Warna           | white   |
| • Jenis liner   | PE-coated paper |                   |         |

### Properti / Nilai Kinerja

- |  |       |                                       |       |
|--|-------|---------------------------------------|-------|
| • Durasi ketahanan suhu jangka panjang | 60 °C | • Durasi ketahanan suhu jangka pendek | 80 °C |
|--|-------|---------------------------------------|-------|

### Adhesi pada Nilai

- |                                  |          |                             |          |
|----------------------------------|----------|-----------------------------|----------|
| • Daya rekat ke Aluminium (awal) | 6.4 N/cm | • Daya rekat ke PVC (awal)  | 3 N/cm   |
| • Daya rekat ke PE (awal)        | 1.4 N/cm | • Daya rekat ke Baja (awal) | 5.5 N/cm |



# tesa<sup>®</sup> 55576

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=55576>