




tesa® 60333

Product Information



tesa® 60333 30 µm single sided matte black single sided electrically conductive copper tape

Deskripsi Produk

tesa® 60333 is matte black single sided electrically conductive copper tape. It consists of electrically conductive matte black copper backing and single sided conductive adhesive coating layer. Designed for EMI shielding for display, FPC, MLB and other components applications.

Product Features

- Excellent matte black appearance
- Excellent electrical conductivity in XYZ-direction
- Excellent EMI shielding performance
- Good bonding strength
- Good heat spreading performance with copper backing

Penerapan

- Display covering and shielding
- MLB shielding
- FPC shielding
- Matte black shielding and covering on component

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Konstruksi Produk

- | | | | |
|-------------------|---------------------|-------------------|-------------|
| • Penyangga | black-coated copper | • Warna | matte black |
| • Jenis perekat | conductive acrylic | • Ketebalan liner | 100 µm |
| • Jenis liner | PET film | • Warna liner | translucent |
| • Ketebalan total | 30 µm | | |

Properti / Nilai Kinerja

- | | | | |
|--|------------------------|---|------------------|
| • Ketahanan kontak arah-z (awal) | 0.05 Ohm / square inch | • Ketahanan permukaan arah x-y (sisi penyangga) | 0.1 Ohm / square |
| • Ketahanan permukaan arah x-y (perekat) | 0.1 Ohm / square | • Tingkat gloss (60°) | 1.1 GU |

Adhesi pada Nilai

- Daya rekat ke Baja (awal) 4 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=60333>



tesa[®] 60333

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60333>