




tesa® 54994

제품 정보



Parmanent Paint Protection Die-Cuts

제품 설명

tesa® 54994 are customized die-cut solutions based on material of tesa® 52994

tesa® 52994 is a single sided transparent protection film with a clear gloss aliphatic polyurethan backing, a permanent acrylic adhesive and a polyester liner.

We are specialized in customizing the shapes and sizes of our products according to individual specifications and customer preferences.

특성

- Highly transparent product design
- Perfect optical clarity makes the film virtually invisible when applied to painted surfaces
- Resistant and durable against mechanical and environmental forces
- Additional topcoat provides outstanding gloss and enhances its exterior durability
- long-term UV resistance and self-healing properties without turning yellow over the vehicle's lifetime
- Good conformability makes it ideal for curves and complex surface geometries
- Dimension stability and die-cuttability
- Compatible with several paint and clearcoat systems
- customized die-cut solutions with visual positioning features help the workers to determine the exact position

Applications

Depending on the car design, there are certain areas that are highly vulnerable to mechanical damage, scratches and corrosion. tesa® 54994 Permanent Paint Protection Films can be applied to protect these high impact areas of the vehicle without changing its design features.

tesa® 54994 is applied to permanently protect sensitive surfaces against strong mechanical forces in interior and exterior applications. It is specially designed for permanent paint protection against stone chipping, abrasion, scratches and corrosion in automotive applications e.g.

- wheel arches
- door edges
- side skirts
- door sill trims
- trunk edges
- front and rear bumpers
- VIN labels
- ...

Due to its good conformability, it can be applied to even and slightly curved surfaces.

관련제품 최신자료는 다음의 경로를 클릭하세요 <http://l.tesa.com/?ip=54994>



tesa® 54994

제품 정보

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

• Backing material Grid	PU 필름	• 총두께	260 µm
• Type of adhesive Grid	아크릴	• 컬러	투명성, 광학적으로 투명한
• Type of liner Grid	PET 필름		

속성 / 성능 값

• 연신률	340 %	• 내화학성	very good
• 내열성 (30분)	90 °C		

추가정보

tesa® 54994 is available in different thicknesses

- tesa® 54994 PV5 - 187 µm
- tesa® 54994 PV0 - 260 µm
- tesa® 54994 PV3 - 360 µm

For more details, please refer to product information of tesa® 52994 PV0, PV3 and PV5.

공지사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다



관련제품 최신자료는 다음의 경로를 클릭하세요 <http://l.tesa.com/?ip=54994>