



# 73322 TP-X (EA)



## 제품 정보

Foam plate mounting tape: FLEX Product Design

## 제품 설명

Double-sided foam tape

## 특성

- Foam properties: Long lasting, constant recovery characteristics. Low thickness tolerance.
- Adhesive properties: Medium tack surface characteristics. Sufficient plate bonding. Easy plate demounting. Excellent tape bonding towards sleeve side.
- Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves.

## Applications

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## 제품 구조

• 기재 소재	PE foam with film lamination	• 총두께	550 µm
• 점착제 종류	변성 아크릴	• 컬러	적색
• 이형지 종류	PP		

## 속성 / 성능 값

• 경도	연한	• 폼 색상	적색
• 두께 범주	500		

## 추가정보

Available liner options:

- PV0: White embossed PP-liner
- PV21: Transparent structured easy application (EA) PET liner for excellent air removal during plate and tape mounting



# 73322 TP-X (EA)

제품 정보

## 공지사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다



관련제품 최신자료는 다음의 경로를 클릭하세요 <http://l.tesa.com/?ip=73322>