



tesa® EasySplice 51405 EasySplice LabellLine Film



Product Information

Double-sided splicing tape

Product Description

tesa® 51405 EasySplice LabellLine Film is a double-sided integrated flying splice tape consisting of a flat-back paper and a modified synthetic rubber adhesive.

Color: Pink

Product Features

- Very good tack properties
- Very high shear resistance on polymer substrates
- Very good adhesion values on polymer substrates
- Low splice thickness
- Printable and coatable backing
- One splitting strip with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process
- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel

Application Fields

tesa® 51405 EasySplice LabellLine Film is particularly suitable for:

- Flying splices of polymer face stocks and backing materials in the label stock industry

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|----------------------|
| • Backing | Paper | • Type of liner | bi-siliconised paper |
| • Type of adhesive | synthetic rubber | • Total thickness | 120 µm |

Properties/Performance Values

- | | | | |
|-----------------------|-----|--------------------|---------|
| • Elongation at break | 6 % | • Tensile strength | 30 N/cm |
|-----------------------|-----|--------------------|---------|

For latest information on this product please visit <http://l.tesa.com/?ip=51405>



tesa[®] EasySplice 51405 EasySplice LabelLine Film

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51405>