



51913 PV11



Product Information

Vannoppløselig, dobbeltklebende skjøtetape

Produktbeskrivelse

tesa® 51913 er en tynn dobbeltsidig resirkulerbar tape, som består av silkepapir og et modifisert vannoppløselig akrylklebestoff.

tesa® 51913 viktige egenskaper

- Gode klebeegenskaper
- Kleber veldig godt til bestrøket og ubestrøket papir
- Meget høy skjærefasthet
- Meget god klebemotstand
- Lav skjøtetykkelse
- Gode resirkuleringsegenskaper i full pH-område (pH3-pH9)

Farge: Blå, fargeløs

Funksjoner

- Very high shear strength
- Very high heat resistance
- Very good adhesion values on most paper grades
- tesa® CaRes 51913 is certified by independent laboratories for: Repulpability according to TAPPI UM-213 over full pH-range (pH3 – pH9)
- The patented calcium resistant adhesive (CaRes) for a maximised life time of permanent splices on papers containing calcium carbonate (CaCO₃)
- Paper from well-managed certified forests and other controlled sources

Applikasjon

tesa® 51913 passer spesielt til

- Permanent overlappende skjøting
- Flygende skjøte i ark- eller satineringsmaskiner
- Kjernestart



51913 PV11

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------------------------|------------------|-------|
| • Bæremateriale | Non-woven | • Total tykkelse | 65 µm |
| • Klebetype | repulpable tackified acrylic | • Farge | Blå |
| • Type liner | repulpable siliconised paper | | |

Egenskaper / ytelsesverdier

- | | | | |
|----------------------------------|-----------|---------------------------|-----------|
| • Klebeevne | medium | • Statisk strekkholdkraft | very good |
| • Lagringstid (emballert) < 25°C | 12 months | | |

Additional Information

Other products for permanent overlapped splicing:

- tesa® 51912 - better bonding on heavier paper grades

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51913>