



tesa® 51915

Product Information



Vannoppløselig, dobbeltklebende tynn-skjøtetape

Produktbeskrivelse

tesa® 51915 er en veldig tynn dobbeltsidig resirkulerbar transfertape, som har et modifisert vannoppløselig akrylklebestoff.

tesa® 51915 viktige egenskaper

- Meget gode klebeegenskaper
- Kleber veldig godt til bestrøket og ubestrøket papir
- Veldig lav skjøtetykkelse
- Gode resirkuleringssegenskaper i full pH-område (pH3-pH9)

Farge: Blå, fargeløs

Funksjoner

- Very high tack properties
- Very good adhesion values on coated and uncoated paper
- Very low splice thickness
- Good repulpability over full pH-range (pH3 –pH9)

Applikasjon

tesa® 51915 passer spesielt til

- Flygende skjøter i papirproduksjons og -omformingsindustrien
- Brukes i hånddispensere eller automatiske prosesser
- Skjøting av karbonfritt papir

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------------------------|------------------|------------------------------|
| • Bæremateriale | Ingen | • Type liner | repulpable siliconised paper |
| • Klebetype | repulpable tackified acrylic | • Total tykkelse | 50 µm |

Egenskaper / ytelsesverdier

- | | | | |
|----------------------------------|-----------|---------------------------|--------|
| • Klebeevne | very good | • Statisk strekkholdkraft | medium |
| • Lagringstid (emballert) < 25°C | 12 months | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51915>



tesa[®] 51915

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51915>