



tesa[®] 4330

Product Information



Høykvalitets maskeringstape til lakkerings arbeide ved ovnstørking opp til 140 °C

Produktbeskrivelse

tesa[®] 4330 er en lett kreppt, fleksibel, vannfast maskeringstape med høy elastisk styrke.

Sustainable Aspects

48% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Funksjoner

- tesa[®] 4330 is a fine crepe paper masking tape combined with a high adhesion and temperature resistant natural rubber adhesive.
- It is the ideal solution for high demanding automotive paint jobs (water- or solvent based paints) with subsequent oven-drying up to 140°C.
- The natural rubber adhesive provides high tack and high adhesion and to a variety of surfaces like paint, metal, glass, rubber and plastic.
- Paint and filler systems adhere excellent to the reverse side avoiding any kind of flaking.
- The fine crepe paper backing has an excellent conformability and enables good cornering.

Applikasjon

Andre bruksområder er f.eks.:

- Maskering av kretskort før plattering
- Kabelbunting
- Pakking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 48 % |
| • Klebetype | Naturgummi | • Total tykkelse | 175 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04330>



tesa[®] 4330

Product Information

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|---------|--------------------|-----------|
| • Bruddforlengelse | 12 % | • Hand tearability | very good |
| • Bruddstyrke | 42 N/cm | • Lett å fjerne | Ja |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 4.8 N/cm |
|---------------------|----------|

Additional Information

Denne tapen garanterer skarpe kanter grunnet dens fine kreppeete struktur. Maling og kitt kleber veldig godt til denne tapen.

tesa[®] 4330 kan lett fjernes uten å etterlate seg rester.

tesa[®] 4330 er også tilgjengelig for omforming og formtilskjæring med papirinnlegg (4330 PV1).

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04330>