



# tesa<sup>®</sup> 4120 Professional

## Product Information

### Universal Pakketape

#### Produktbeskrivelse

tesa<sup>®</sup> 4120 er en pakketape som er basert på et bæremateriale av polyvinylklorid-folie i kombinasjon med en kleber av naturgummi. Kleberen av naturgummi sikrer svært gode vedheftningsegenskaper på forskjellige overflater, og kan fjernes igjen uten å etterlate rester. tesa<sup>®</sup> 4120 tape er ideell til manuelt forseglingsutstyr. Tapen kan også brukes med en automatisk forseglingsmaskin. Høy gripeevne og kort forankringstid sikrer optimal sikkerhet for pappesken umiddelbart etter at tapen er påført. Tapen er behagelig å bruke i tillegg til at den er enkel, stabil og støysvak å rulle av. tesa<sup>®</sup> 4120 tape er trykkbar og fås i hvit, brun og transparent.

#### Funksjoner

- The natural rubber adhesive system offers very good adhesive properties to various surfaces and can be removed without leaving behind any residue.
- tesa<sup>®</sup> 4120 tape is ideal for manual sealing equipment, though it can also be used with an automatic sealing machine.
- The tape is convenient to use, and unwinds smoothly, steadily, and quietly.

#### Applikasjon

- tesa<sup>®</sup> 4120 brukes til manuell lukking av middels tunge pappesker
- Tapen kan også benyttes med automatisk forseglingsutstyr
- Enkel og støysvak avrulning gjør tapen ideell til behagelig bruk i stor skala i mange forskjellige bransjer
- Høy gripeevne og kort forankringstid sikrer raskt og pålitelig hold

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Produktinnhold

- |                 |            |                  |       |
|-----------------|------------|------------------|-------|
| • Bæremateriale | PVC-film   | • Total tykkelse | 49 µm |
| • Klebetype     | Naturgummi |                  |       |

#### Egenskaper / ytelsesverdier

- |                        |           |                              |             |
|------------------------|-----------|------------------------------|-------------|
| • Bruddforlengelse     | 75 %      | • Manuel påsetting           | Ja          |
| • Bruddstyrke          | 43 N/cm   | • Packaging Weight           | Up to 25 kg |
| • Automatisk påsetting | Ja        | • Silent unwinding           | Ja          |
| • Hand tearability     | very good | • Suitable for deep freezing | Ja          |

#### Klebekraft

- |                     |        |
|---------------------|--------|
| • Klebeevne på Stål | 2 N/cm |
|---------------------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=04120>



# tesa<sup>®</sup> 4120 Professional

Product Information

## Additional Information

tesa<sup>®</sup> 4120 er lett å sette trykk på. Tilgjengelige farger: hvit, havannabrun og transparent

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04120>