




NOPI® 4349

Product Information



Papirbasert tape for generell bruk

Produktbeskrivelse

NOPI® 4349 er en papirbasert tape for generell bruk, og er basert på et bæremateriale av lett kreppt papir og et klebemiddel i naturgummi. Den papirbaserte tapen egner seg for generelle applikasjoner som merking, fastholdelse, forsegling, fiksering og emballering av lette esker.

Sustainable Aspects

58% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Funksjoner

- Bærematerialet i kreppt papir sikrer god formbarhet.
- Klebemiddelsystemet i naturgummi har god vedheft og gripeevne på ulike overflater som blant annet metall, glass og gummi.

Applikasjon

Produktet er egnet for generelle applikasjoner som bl.a. fastholdelse, forsegling, fiksering og emballering.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 58 % |
| • Klebetype | Naturgummi | • Total tykkelse | 110 µm |

Egenskaper / ytelsesverdier

- | | | | |
|---------------------------------------|-----------------------|---------------------------------------|-----------------------|
| • Bruddforlengelse | 10 % | • Avrullingskraft (Rull bredde ≤ 9mm) | 2.5 N/roll (30 m/min) |
| • Bruddstyrke | 33 N/cm | • Hand tearability | very good |
| • Avrullingskraft (Rull bredde > 9mm) | 2.5 N/roll (30 m/min) | | |

For latest information on this product please visit <http://l.tesa.com/?ip=04349>



NOPI® 4349

Product Information

Klebekraft

• Klebeevne på ru overflater

0.6 N/cm

• Klebeevne på Stål

2 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04349>