



tesa[®] 51432

Product Information



Sekvenseringstape/bandoleringstape

Produktbeskrivelse

For lager- og sekvenssammenbinding i kombinasjon med kreppet bandoleringstape.

Funksjoner

- Dimensionally stable and smooth paper backing for excellent belting performance
- Strong natural rubber adhesive with excellent adhesive properties on different substrates
- Can be used for storage- and sequencer-belting in combination with crepe paper belting tapes
- Due to the strong adhesive and dimensionally stable and smooth paper backing tesa[®] 51432 is ideally suited for belting of heavy components.

Applikasjon

Den dimensjonsmessige stabile glatte papirmaterialet gjør produktet særlig egnet til bandolering av tunge komponenter.

Spesielt for sekvensbandolering, hvor det kreves mer ubøyelige belter.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------|------------------|--------|
| • Bæremateriale | Papir (Glatt) | • Total tykkelse | 330 µm |
| • Klebetype | Naturgummi | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|-----|---------------|---------|
| • Bruddforlengelse | 6 % | • Bruddstyrke | 93 N/cm |
|--------------------|-----|---------------|---------|

Klebekraft

- | | |
|---------------------|--------|
| • Klebeevne på Stål | 8 N/cm |
|---------------------|--------|



tesa[®] 51432

Product Information

Additional Information

tesa[®] 51432 kan kombineres med tesa[®] 51300 eller 51316.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51432>