



# tesa<sup>®</sup> 4302

## Product Information



Kraftig maskeringstape til bruk ved temperaturer opp til 160 °C

### Produktbeskrivelse

tesa<sup>®</sup> 4302 er en lett kreppt og tilpassningsvennlig papirmaskeringstape, som er særlig velegnet til ytterst krevende lakeringsoppgaver i automobilindustrien (vann- eller løsemiddelbaserte lakker) etterfulgt av ovnstørking.

Lakk og selv kritiske sparkelmasser hefter godt til bærematerialet, så enhver avskalling unngås.

tesa<sup>®</sup> 4302 kan fjernes fra gummi, glass og maling uten å briste eller etterlate kleberester. Dette er særlig bemerkelsesverdig, idet det også gjelder ved avmaskering på kalde overflater etter perioder med høye temperaturer.

Takket være den lett kreppepe struktur gir denne tape en finish med skarpe kanter.

### Sustainable Aspects

70% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

### Funksjoner

- Natural rubber adhesive provides high tack and adhesion to a variety of surfaces like paint, metal, glass, rubber and plastic.
- Smooth-to-touch paper backing with excellent conformability enabling good cornering.
- Can be removed without any residues or tearing even after cooling down.

### Applikasjon

Suitable for masking applications in high demanding automotive paint jobs with subsequent oven drying up to 160 °C / 1h.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |                     |  |        |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 70 %   |
| • Klebetype     | Naturgummi          | • Total tykkelse   | 170 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04302>



# tesa<sup>®</sup> 4302

## Product Information

### Egenskaper / ytelsesverdier

- |                    |         |                    |           |
|--------------------|---------|--------------------|-----------|
| • Bruddforlengelse | 10 %    | • Hand tearability | very good |
| • Bruddstyrke      | 46 N/cm | • Lett å fjerne    | Ja        |

### Klebekraft

- |                     |        |
|---------------------|--------|
| • Klebeevne på Stål | 4 N/cm |
|---------------------|--------|

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04302>