



tesa® 60672

Product Information



Robust aluminiumstape med dekkpapir – 75 µm tykk staniol

Produktbeskrivelse

tesa® 60672 er en robust aluminiumstape basert på 75 µm tykk staniol, en transparent akrylkleber samt et hvitt, enkeltklebende og silikonbelagt dekkpapir, som er 85 µm tykt.

Detaljer:

- Mekanisk bestandig
- Enkel å rulle ut
- Passer til permanente anvendelser
- Barrierer mot fukt, gasser og damper
- Elektrisk og termisk ledende
- Aldersbestandig
- Varme- og lysreflekterende
- Brannhemmende i henhold til DIN 4102, klasse B1
- Brannhemmende i henhold til kravene i UL 510A

Funksjoner

- Mechanical stable
- Easily removable liner
- Suitable for permanent applications
- Barrier against moisture, gases and vapors
- Electrically and thermally conductive
- Aging resistant
- Heat and light reflective
- Flame retardant according to DIN 4102, class B1
- Flame retardant according to the requirements in UL 510A
- Meets requirements of UL723

Applikasjon

- Reparasjoner på lastebiler og trailere
- Sammenføyning og tetning av varmeisolering, kanaler og rør
- Gjør materialer elektrisk og termisk ledende
- Til reflektering av varmestråling
- Lett avtakelig dekkpapir
- Oppfyller kravene for UL723



tesa[®] 60672

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

• Bæremateriale	Aluminiumsfolie	• Linerfarge	Hvit
• Klebetype	Akryl	• Linertykkelse	85 µm
• Type liner	Papir	• Tapetykkelse	_NULL µm
• Total tykkelse	125 µm		

Egenskaper / ytelsesverdier

• Bruddforlengelse	8 %	• Lett å fjerne	Nei
• Bruddstyrke	60 N/cm	• Slippkraft for dekkpapir	0.3 N/cm
• Driftstemperatur fra	-40 °C	• Slitstyrkebestandighet	very good
• Driftstemperatur opp til	160 °C	• Temperature resistance min.	-40 °C
• Egnet til utstansing	Ja	• Water resistance	very good
• Hand tearability	very good		

Klebekraft

• Backing	9 N/cm	• Klebeevne på PVC (umiddelbart)	7 N/cm
• Klebeevne på Glass (Umiddelbart)	10 N/cm	• Klebeevne på Stål	10 N/cm
• Klebeevne på PE (umiddelbart)	5.5 N/cm		



tesa[®] 60672

Product Information

Additional Information

The total thickness given in the section "Technical Data" describes the thickness of the tape without liner. The thickness with liner is 210 µm (8.3 mil).

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60672>