




tesa[®] 50650

Formbar



Product Information

Blå maskeringstape av polyester med silikonkleber

Produktbeskrivelse

tesa[®] 50650 er en blå tape for høye temperaturer av polyester med silikonklebestoff. Den har følgende egenskaper:

- Meget resistent overfor høye temperaturer
- Skarp malekant
- Meget tilpasningsbar til bruk på ujevne former
- Kan fjernes uten rester

Funksjoner

- High temperature resistance (up to 220°C for 30 minutes)
- Residue-free removability for masking and surface protection applications
- Good conformability, thin backing for sharp color edges
- The high-temperature tape features easy application and easy one-piece removal without leaving residues behind.
- The thin tape conforms well around irregular shapes, enables sharp color edges and offers excellent paint anchorage.

Applikasjon

Maskering av områder som ikke skal males under legging av pulverbelegg.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------|------------------|-------|
| • Bæremateriale | PETP | • Total tykkelse | 55 µm |
| • Klebetype | Silikon | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|---------|-----------------------------------|--------|
| • Bruddforlengelse | 120 % | • Lett å fjerne | Ja |
| • Bruddstyrke | 50 N/cm | • Temperaturbestandighet (30 min) | 220 °C |
| • Hand tearability | low | | |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 3.3 N/cm |
|---------------------|----------|



tesa[®] 50650

Formbar

Product Information

Additional Information

tesa[®] 50650 er også tilgjengelig med PET-innlegg.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50650>