



tesa® 51616 ID

Product Information



Tape av tykk PET-fleece kraftig lyddempning av ledningsnett

Produktbeskrivelse

tesa® 51616 er en kostnadseffektiv tape som gir god lyddemping og høy slitasjemotstand. Den er optimert til manuelt bruk på kabelfester.

Egenskaper:

- Kan rives for hånd
- Meget god lyddemping
- Resistent ved 125#/3000 t
- Alder-resistent
- Råtnesikker
- Kraftig klebeevne
- Fleksibel og glatt

Funksjoner

- High noise damping
- High abrasion resistance
- Handtearable
- Identifier solution

Applikasjon

Kabelfesting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|--------------|------------------|--------|
| • Bæremateriale | PET-flis | • Type liner | PP |
| • Klebetype | Gummi basert | • Total tykkelse | 650 µm |

Produktsortiment

- | | |
|------------------------|--------------|
| • Tilgjengelige farger | svart / hvit |
|------------------------|--------------|



tesa[®] 51616 ID

Product Information

Egenskaper / ytelsesverdier

• Bruddforlengelse	35 %	• Color of logo	lilla
• Bruddstyrke	30 N/cm	• Hand tearability	Ja
• Abrasion resistance (10mm mandrel, LV312)	Class D	• Hardhet	Medium
• Abrasion resistance (5mm mandrel, LV312)	Class C	• Lyddempning (LV312)	Class D
• Avrullingskraft (Rull bredde > 9mm)	12 N/roll (30 m/min)	• Temperature resistance max.	105 °C
• Avrullingskraft (Rull bredde ≤ 9mm)	12 N/roll (30 m/min)	• Temperature resistance min.	-40 °C

Klebekraft

- Klebeevne på Stål 3 N/cm

Lagringsforhold

Lagringsforhold

- Storage temperature: 23°C (+/-10°C)
- Relative humidity: recommended 40–60% (room climate)
- Product guarantee: tesa guarantees a maximum shelf life of 12 months from date of dispatch (based on ISO 554)

Additional Information

Temperaturmotstand målt ved 30000 t ifølge LV312

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=NaN>