



# tesa® 4338

## Product Information



### tesa® 4338 Maskeringstape til høye temperaturer

#### Produktbeskrivelse

tesa® 4338 er en grønn tape for krevende maskeringsoppgaver i transportsektorer som marine, tog, lastebil og flere andre der det kreves høy fleksibilitet og skarpe malingskanter.

Tapen er lett å rulle av og er fingervennlig. Den er velegnet til å lage gode, skarpe kanter – og selv etter sju dager utendørs og seks tørkesykluser på 40 minutter i ovnen ved 120 °C kan tapen lett fjernes uten å etterlate rester.

#### Sustainable Aspects

54% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

#### Funksjoner

- The aging resistant natural rubber adhesive has a good quick stick, provides outdoor usability for up to seven-days, temperature resistance up to 120 °C / 248 F and clean removal.

#### Applikasjon

- Høy synlighet på grunn av den klare grønnfargen
- Lett å håndtere (enkel og kontrollert avrulling, fingervennlig og høy fleksibilitet)
- Kan brukes i flere tørkesykluser - opp til seks ved 120 °C / 40 min
- God initial klebekraft for å sikre pålitelig dekning
- Rene og skarpe malekanter
- UV-bestendig i opptil 14 dager\*

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Produktinnhold

- |                 |                     |  |        |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 54 %   |
| • Klebetype     | Naturgummi          | • Total tykkelse   | 145 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04338>



# tesa<sup>®</sup> 4338

## Product Information

### Egenskaper / ytelsesverdier

- |                    |         |                    |           |
|--------------------|---------|--------------------|-----------|
| • Bruddforlengelse | 13 %    | • Hand tearability | very good |
| • Bruddstyrke      | 43 N/cm | • Lett å fjerne    | Ja        |

### Klebekraft

- |                     |          |
|---------------------|----------|
| • Klebeevne på Stål | 3.5 N/cm |
|---------------------|----------|

### Additional Information

\*UV-bestendig i opptil 14 dager i Sentral- og Nord-Europa

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04338>