



tesa[®] extra Power Universell

Product Information



BNR 56348, 56338, 56389, 56388, 56380, 56490, 56396

Produktbeskrivelse

tesa[®] extra Power Universal er en allsidig elektrikertape med ekstra vedheft. Ideell for håndverk, reparasjon, festing, bunting og merking og mer.

Funksjoner

- For håndverk, reparasjon, festing, bunting, forsterking, merking og mye mer
- For daglige, ukompliserte løsninger og raske og enkle reparasjoner
- Meget god vedheft til alle typer overflater
- Værbestandig for bruk både inne og ute
- Kan rives for hånd
- Løsemiddelfri

Applikasjon

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|--------------------------|------------------|--------|
| • Bæremateriale | PE-film med PET filament | • Total tykkelse | 215 µm |
| • Klebetype | Syntetisk gummi | | |



tesa[®] extra Power Universell

Product Information

Egenskaper / ytelsesverdier

• Bruddstyrke	46.3 N/cm	• Materiale	PE (polyetylen)
• Aldringsbestandighet (UV)	Ja	• Miljøvennlig emballasje	Nei
• Application temperature from	10 °C	• Motstandsdyktig overfor olje og fett	Ja
• Application temperature to	50 °C	• Ozone resistance	Ja
• Batterier inkl.	Nei	• Reservedelsservice	Nei
• Bruksområde	Garasje, Bil, Hjemme, Hage	• Rivebestandig	Ja
• Bruksområdet	Innendørs og utendørs	• Skrivbar	Nei
• Farlig materiale	Nei	• Spennbarhet	19 %
• Fjernes uten kleberester	Nei	• Temperaturbestandighet	Ja
• Fuktbestandighet	Ja	• Temperature resistance max.	95 °C
• Hand tearability	Ja	• UV-bestandig	Ja
• Kan brukes om igjen	Nei	• Vanntett	Ja
• Klebekraft	Høy vedheft	• Velegnede overflater	Jevnt tre, Fliser, De fleste plasttyper, Glass, Metall
• Krever batterier	Nei	• Water resistance	Ja
• Løsemiddelfri	Ja		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>