



# tesa® Limkrok for gjennomsiktige flater og glass 1 kg



## Product Information

BNR 77735

## Produktbeskrivelse

Gjennomsiktig selvklebende krok som holder opptil 1 kg per krok. Usynlig montering for dekorasjoner og middels tunge objekter på gjennomsiktige og faste overflater som glass.

## Funksjoner

- For gjennomsiktige og faste innendørs overflater
- For gjenstander med middels vekt på opptil 1 kg per krok
- Kan fjernes uten å etterlate merker
- Gjenbrukbar med en ny strimmel\* Begrenset UV-bestandighet

## Applikasjon

- How to apply – Step by step1. Clean the surface with silicone-free window cleaner or methylated spirit. Make sure the surface is dry before application
2. Apply the Adhesive Strip first to the rougher surface. Be careful not to touch the adhesive area at any time.
  3. Apply the hook, also pressing on it evenly all over for at least 5 seconds.
  4. Make sure the tab is accessible for easy removal.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Produktinnhold

- |                                |                 |                |             |
|--------------------------------|-----------------|----------------|-------------|
| • Klebetype                    | Syntetisk gummi | • Krokens form | Rektangulær |
| • Holding power of strip up to | 1 Kg            | • Uten silikon | Ja          |
| • Klebekraft opp til           | 1 Kg            |                |             |



# tesa<sup>®</sup> Limkrok for gjennomsiktige flater og glass 1 kg

## Product Information

### Egenskaper / ytelsesverdier

|                                |                                     |                                        |                                                                          |
|--------------------------------|-------------------------------------|----------------------------------------|--------------------------------------------------------------------------|
| • Application temperature from | -15 °C                              | • Løsemiddelfri                        | Ja                                                                       |
| • Batterier inkl.              | Nei                                 | • Materiale                            | PS (polystyren)                                                          |
| • Bruksområdet                 | Innendørs                           | • Motstandsdyktig overfor olje og fett | Nei                                                                      |
| • Farlig materiale             | Nei                                 | • Ozone resistance                     | Ja                                                                       |
| • Fjernes uten kleberester     | Ja                                  | • Temperature resistance max.          | 35 °C                                                                    |
| • Fuktbestandighet             | Nei                                 | • Temperature resistance min.          | 5 °C                                                                     |
| • Kan brukes om igjen          | Ja                                  | • UV-bestandig                         | Ja                                                                       |
| • Kan brukes om igjen med      | Adhesive Strip 1,0kg<br>Transparent | • Vanntett                             | Nei                                                                      |
| • Kjemikaliebestandig          | Nei                                 | • Velegnede overflater                 | Jevnt tre, Fliser, De fleste plasttyper, Glass, Akrylglass, Stål, Metall |
| • Krever batterier             | Nei                                 |                                        |                                                                          |

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>