



tesa[®] extra Power Perfekt

Product Information

BNR 56343, 56341, 56342, 56344, 56339

Produktbeskrivelse

tesa cloth tape extra Power Perfect er en premium kvalitets reparasjonstape, utviklet for krevende innendørs og utendørs bruk.

Funksjoner

- Bruk stofftape på alle profesjonelle løsninger innen håndverk, festing, bunting, forsterking, merking og mye mer
- Best, og perfekt vedheft, også på ujevne og oljete overflater
- For permanent høy elastisitet og langvarige resultater
- Værbestandig stofftape for bruk både inne og ute
- Rivebestandig, men kan rives av for hånd
- Kan skrives på
- Tilgjengelig i et bredt spekter av farger

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------------|------------------|--------|
| • Bæremateriale | Akrylbelagt tekstil | • Total tykkelse | 310 µm |
| • Klebetype | Naturgummi | | |



tesa[®] extra Power Perfekt

Product Information

Egenskaper / ytelsesverdier

• Bruddstyrke	100 N/cm	• Løsemiddelfri	Ja
• Aldringsbestandighet (UV)	Ja	• Miljøvennlig emballasje	Ja
• Application temperature from	+10 °C	• Motstandsdyktig overfor olje og fett	Ja
• Application temperature to	+50 °C	• Ozone resistance	Ja
• Batterier inkl.	Nei	• Reservedelsservice	Nei
• Bruksområde	Garasje, Bil, Hjemme, Hage	• Rivebestandig	Ja
• Bruksområdet	Innendørs og utendørs	• Skrivbar	Ja
• Farlig materiale	Nei	• Spennbarhet	13 %
• Fjernes uten kleberester	Ja	• Temperaturbestandighet	Ja
• Fuktbestandighet	Ja	• Temperature resistance max.	140 °C
• Hand tearability	Ja	• UV-bestandig	Ja
• Kan brukes om igjen	Nei	• Vanntett	Ja
• Klebekraft	Svært høy vedheft	• Velegnede overflater	Jevnt tre, Fliser, Murstein, De fleste plasttyper, Glass, Akrylglass, Kartong, Gips, Papir, Metall, Stål, Stein
• Krever batterier	Nei	• Water resistance	Ja

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>