



tesa[®] Monteringstape for gjennomsiktig flate og glass 20kg / m



Product Information

BNR 77741, 77740

Produktbeskrivelse

Monteringstape for gjennomsiktig flate og glass som holder opptil 20kg / m En nesten usynlig, varig løsning for montering av gjenstander på gjennomsiktige og faste overflater.

Funksjoner

- For gjennomsiktige og faste innendørs overflater
- Holder opptil 20 kg / m*
- For permanente bruksområder
- Nesten usynlig
- For optimale resultater er maks. 6 kg per bruksområde/gjenstand anbefalt

Applikasjon

How to apply – Step by step1. To ensure the best possible bond, the object and the surface must be free of dust, dirt and grease. To clean them, use a brush or a lint-free cloth and a silicone-free cleaner like methylated spirits. Make sure the surface is dry before application.

2. Check if the surface or the object is rougher and apply the mounting tape to the rougher surface.
3. Apply the tape in vertical strips along the full length of the object or surface. Reinforce the upper portion with shorter strips, since that's where most of the load will be born.
4. Press down firmly across the entire surface of Mounting Tape for at least five seconds. Remove the protective film, taking care not to touch the exposed adhesive surface as this could affect the adhesion.
5. Fix the object and press it again at least five seconds.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|------------------|-----------------|-----------------------------|---------|
| • Klebetype | Syntetisk gummi | • Tapens klebekraft opp til | 20 KG/M |
| • Total tykkelse | 500 µm | | |



tesa[®] Monteringstape for gjennomiktig flate og glass 20kg / m

Product Information

Egenskaper / ytelsesverdier

• Application temperature from	-10 °C	• Løsemiddelfri	Ja
• Batterier inkl.	Nei	• Materiale	_NULL
• Bruksområdet	Innendørs	• Motstandsdyktig overfor olje og fett	Nei
• Farlig materiale	Nei	• Ozone resistance	Ja
• Fjernes uten kleberester	Nei	• Temperature resistance max.	40 °C
• Fuktbestandighet	Nei	• Temperature resistance min.	10 °C
• Kan brukes om igjen	Nei	• UV-bestandig	Ja
• Kan brukes om igjen med	_NULL	• Vanntett	Nei
• Kjemikaliebestandig	Nei	• Velegnede overflater	Jevnt tre, Fliser, De fleste plasttyper, Glass, Akrylglass, Stål, Metall
• Krever batterier	Nei		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>