



# tesa<sup>®</sup> Monteringstape for fliser og metall 100kg/m



## Product Information

BNR 77746, 77747

## Produktbeskrivelse

Monteringstape for fliser og metaller opptil 100 kg/m. Den sterkeste måten å veggmontering på glatte og faste overflater som fliser.

## Funksjoner

- For glatte og faste innendørs overflater som fliser
- Kan inneholde opp til 100 kg/m\*
- For permanente bruksområder
- For optimale resultater er maks. 6 kg per bruksområde/gjenstand anbefalt

## Applikasjon

How to apply – Step by step 1. For the best possible bond, use alcohol or silicone-free window cleaner to make sure your surface is free of dust and grease. Ensure the surface is dry before application.

2. Check whether the surface or the object is rougher and apply the mounting tape to it.

3. Apply the heavy-duty, double-sided tape in vertical strips corresponding to the full length of the object or surface, and press down firmly all along the entire strip for at least 5 seconds. Be careful not to touch the exposed adhesive area.

4. Remove the backing from the tape and position the item on the surface.

5. Press down firmly on the item for at least another 5 seconds to get as close a bond as possible.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Produktinnhold

- |                 |                 |                             |          |
|-----------------|-----------------|-----------------------------|----------|
| • Bæremateriale | PE-skum         | • Total tykkelse            | 1100 µm  |
| • Klebetype     | Syntetisk gummi | • Tapens klebekraft opp til | 100 KG/M |



# tesa<sup>®</sup> Monteringstape for fliser og metall 100kg/m

## Product Information

### Egenskaper / ytelsesverdier

• Application temperature from	-10 °C	• Løsemiddelfri	Ja
• Batterier inkl.	Nei	• Motstandsdyktig overfor olje og fett	Nei
• Bruksområdet	Innendørs	• Ozone resistance	Nei
• Farlig materiale	Nei	• Temperature resistance max.	40 °C
• Fjernes uten kleberester	Nei	• Temperature resistance min.	10 °C
• Fuktbestandighet	Nei	• UV-bestandig	Nei
• Kan brukes om igjen	Nei	• Vanntett	Nei
• Kan brukes om igjen med	_NULL	• Velegnede overflater	Jevnt tre, Fliser, De fleste plasttyper, Glass, Akrylglass, Stål, Metall
• Krever batterier	Nei		

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>