



# tesa<sup>®</sup> Monteringstape for fliser og metaller



## Product Information

BNR 77745, 77744

## Produktbeskrivelse

Monteringstape for fliser og metall er en permanent måte å montere i våtrom som bad. Det holder pålitelig speil og andre gjenstander som er opptil 4 mm tykk.

## Funksjoner

- For glatte og faste innendørs overflater som fliser
- Passer for våtrom som bad
- Spesielt egnet for speil og gjenstander opptil 4 mm tykk
- For permanente bruksområder

## Applikasjon

- How to apply – Step by step1. To ensure the best possible bond, use silicone-free alcohol or window cleaner to make sure both your surface and object are free of dust and grease. Ensure the surface is dry again before application.
2. Check if the surface or the object is rougher and apply the mounting tape to rougher one. Apply the tape in vertical strips that correspond to the full length of the object. Reinforce the upper portion with shorter strips, since that's where the majority of the load will be born.
3. Press down firmly over the entire surface of the Mounting Tape for at least five seconds.
4. Remove the protective foil from the double-sided adhesive tape, taking care not to touch the exposed adhesive surface as this could affect the adhesion.
5. Position the object and press it again firmly at least five seconds.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Produktinnhold

- |                 |         |                  |         |
|-----------------|---------|------------------|---------|
| • Bæremateriale | PE-skum | • Total tykkelse | 1200 µm |
| • Klebetype     | Akryl   |                  |         |



# tesa<sup>®</sup> Monteringstape for fliser og metaller

## Product Information

### Egenskaper / ytelsesverdier

• Application temperature from	-10 °C	• Krever batterier	Nei
• Batterier inkl.	Nei	• Løsemiddelfri	Ja
• Bruksområdet	Innendørs	• Motstandsdyktig overfor olje og fett	Nei
• Farlig materiale	Nei	• Ozone resistance	Nei
• Fjernes uten kleberester	Nei	• Temperature resistance max.	40 °C
• Fuktbestandighet	Ja	• Temperature resistance min.	10 °C
• Kan brukes om igjen	Nei	• UV-bestandig	Nei
• Kan brukes om igjen med	_NULL	• Vanntett	Nei
• Kjemikaliebestandig	Ja	• Velegnede overflater	Fliser, De fleste plasttyper, Glass, Metall, Stål

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>