



tesa® Limspiker for tapet og gips 1 kg

Product Information



BNR 77773

Produktbeskrivelse

Limspiker for opptil 1 kg. Ideell for opphenging av pyntegjenstander som bilder på strukturerte og sensitive overflater som tapet eller gips.

Funksjoner

- For teksturerte og sensitive overflater som tapet eller gips
- For gjenstander opptil 1 kg* per spiker eller 2 kg ved hjelp av 2 spikrer
- Kan fjernes uten å etterlate merker
- Gjenbrukbar med en ny strimmel
- For optimale resultater kan du lese instruksjonsheftet

Applikasjon

How to apply – Step by step1. Ensure the best possible bond by cleaning the surface of dirt and dust with a dust-free cloth.

2. Apply the Adhesive Strip to the rougher surface. In the case of wallpaper or plaster, always first apply it to the wall, with the blue tab facing the wall. Before using, make sure that your surface is strong enough to take the weight of the object you want to attach.

3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. By pressing down like this, the flexible polymer chains are activated to form U-shaped links with the surface. It's these links that give such a secure and reliable bond, so the harder and more evenly you press, the better the bond.

4. Now apply the tesa® Adhesive Nail by aligning it on the top edge of the strip then folding it down. Press down evenly all over the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or beneath the nail for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|--------------------------------|-----------------|----------------------|------|
| • Klebetype | Syntetisk gummi | • Klebekraft opp til | 1 Kg |
| • Holding power of strip up to | 1 Kg | • Uten silikon | Ja |



tesa® Limspiker for tapet og gips 1 kg

Product Information

Egenskaper / ytelsesverdier

• Application temperature from	-15 °C	• Løsemiddelfri	Ja
• Batterier inkl.	Nei	• Materiale	PS (polystyren)
• Bruksområdet	Innendørs	• Motstandsdyktig overfor olje og fett	Nei
• Farlig materiale	Nei	• Ozone resistance	Nei
• Fjernes uten kleberester	Ja	• Temperature resistance max.	35 °C
• Fuktbestandighet	Nei	• Temperature resistance min.	5 °C
• Kan brukes om igjen	Ja	• UV-bestandig	Nei
• Kan brukes om igjen med	Selvklebende strimmel 1 kg Tapet	• Vanntett	Nei
• Kjemikaliebestandig	Nei	• Velegnede overflater	Gips, Tapet
• Krever batterier	Nei		

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>