



# 51150 FastLine



## Product Information

Vannoppløselig, dobbeltklebende skjøtetape

### Produktbeskrivelse

tesa® 51150 EasySplice® FastLine er en dobbeltsidig integrert resirkulerbar flygende skjøtetape uten innlegg består av flatt papir og et modifisert vannoppløselig akrylklebestoff.

tesa® 51150 EasySplice® FastLine viktige egenskaper:

- De beste klebeegenskaper
- Kleber veldig godt til bestrøket og ubestrøket papir
- Lav skjøtetykkelse
- Trykk- og beleggbart materiale
- Gode resirkuleringsegenskaper i full pH-område (pH3-pH9)

Følgende funksjoner:

- Splitt-innlegg for sikker feste av toppark
- Klebeblending med veldig høy klebeevne for glimrende kontakt mellom enden på papirbane og ny rull
- To splittebånd i papir for jevn åpning av ny papirrull uten å skade bekleddingsprosessen

Farge: Blå

### Funksjoner

- Highest tack properties
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Good repulpability over full pH-range (pH3 – pH9)
- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process

### Applikasjon

tesa® 51150 EasySplice® FastLine passer spesielt til:

- Flygende skjøter ved hurtig kjørende frakoblede bestrykningsmaskiner

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

For latest information on this product please visit <http://l.tesa.com/?ip=51150>



# 51150

## FastLine

### Product Information

#### Produktinnhold

• Bæremateriale	Papir (Glatt)	• Total tykkelse	100 µm
• Klebetype	repulpable tackified acrylic	• Farge	Blå
• Type liner	repulpable siliconised paper		

#### Egenskaper / ytelsesverdier

• Bruddforlengelse	6 %	• Lagringstid (emballert) < 25°C	12 months
• Bruddstyrke	30 N/cm	• Statisk strekkholdkraft	medium
• Klebeevne	good, medium		

#### Additional Information

PV0: 2 split strips with 9mm width each

PV1: 2 split strips with 15mm width each

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51150>