



# 75530

## Product Information



ACX<sup>plus</sup> transparent 3000 µm

### Produktbeskrivelse

tesa® 75530 er en transparent akryltape.

Takket være den høye grad av gjennomsiktighet så er den særlig velegnet til permanent montering av transparente materialer slik som glass eller akryl.

Den viskoelastiske akryltapen kompenserer godt for ulike varmeutvidelser på forskjellige materialer.

### Funksjoner

- Due to its thickness ideal for gap filling requirements

### Applikasjon

Klebing og montering av transparente og gjennomskinnelige materialer: Skilt, glass, paneler, glassvegger etc.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |           |                  |             |
|-----------------|-----------|------------------|-------------|
| • Bæremateriale | Akryl     | • Total tykkelse | 3000 µm     |
| • Klebetype     | Ren akryl | • Farge          | Transparent |

### Klebekraft

- |                                     |         |
|-------------------------------------|---------|
| • Klebeevne på Stål (etter 3 dager) | 30 N/cm |
|-------------------------------------|---------|

### Additional Information

For more technical data please click on the following link to open our technical information sheet:

<https://www.tesa.com/ACX<sup>plus</sup>/TI-sheet>

The product is recommended for indoor and outdoor usage. To ensure the highest performance possible, our aim is to fully understand the application (including the substrates involved) to provide the best product recommendation.

Liner options:

- PV28: Blue film liner – unbranded

For latest information on this product please visit <http://l.tesa.com/?ip=75530>



# 75530

## Product Information

### Additional Information

- PV48: White film liner – branded

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=75530>