



tesa[®] ACXplus 70730

Product Information

ACX^{plus} sort 2900 µm

Produktbeskrivelse

tesa[®] 70730 er en sort akryltape som tåler de høyeste belastninger.

Velegnet til klebning på områder og materialer som er utsatt for meget høy varme og/eller kraftig belastning i kulde og frost.

Den viskoelastiske akryltapen kompenserer for ulike varmeutvidelser ved forskjellige materialer.

Applikasjon

Klebning og montering av emner som utsettes for høye og / eller lave temperaturer: Truck-, kran- og heiskabiner, integrerte solpaneler, produksjonsutstyr etc.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|-----------|------------------|---------|
| • Bæremateriale | Akrylskum | • Total tykkelse | 2900 µm |
| • Klebetype | Ren akryl | • Farge | Sort |

Egenskaper / ytelsesverdier

- | | | | |
|---|--------|---|--------|
| • Temperaturbestandighet, kort varighet | 220 °C | • Temperaturbestandighet, lang varighet | 120 °C |
|---|--------|---|--------|

Klebekraft

- | | |
|-------------------------------------|---------|
| • Klebeevne på Stål (etter 3 dager) | 38 N/cm |
|-------------------------------------|---------|



tesa[®] ACXplus 70730

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=70730>