



# 7044

## Gray / White

### Product Information

1000 µm Dobbeltsidig Akrylskumtape



### Produktbeskrivelse

tesa® 7044 ACX<sup>plus</sup> er en dobbeltsidig akrylskumtape som består av et høytytende akrylsystem. Tapen kjennetegnes først og fremst ved sin sammenføyningsstyrke, belastningsavledende egenskaper samt temperatur- og værbestandighet. Den dobbeltsidige akrylskumtapen kombinerer på grunn av produktets unike sammensetning svært høye vedheftningsnivåer med evnen til å absorbere og spre høye dynamiske belastninger.

Produktets viskoelastiske kjerne er i stand til å kompensere for termisk forlengelse av bundne deler. tesa® ACX<sup>plus</sup> 7044 yter godt på materialer som er vanskelige å sammenføye, som pulverlakkeringer eller kunststoffmaterialer. Selv i forbindelse med kombinasjoner av slike materialer yter dette produktet avansert sikkerhet på grunn av den innovative designen. tesa® ACX<sup>plus</sup> 7044 muliggjør boblefri sammenføyning. De grå eller hvite fargene tilpasser seg veldig fint på overflater av metall og kunststoff, noe som gir en usynlig sammenføyning.

### Funksjoner

- Available in gray and white color
- The color options adapt very well to metal and plastic surfaces to avoid reflections

### Applikasjon

- tesa® ACX<sup>plus</sup> 7044 er velegnet til en lang rekke sammenføyningsanvendelser knyttet til bygg og konstruksjon, herunder:
  - Dekorative paneler (f.eks. kjøleskapsdører av glass)
  - Dekorative elementer (f.eks. forsidene på oppvaskmaskiner, sprosser på vinduer)
  - Anvendelser med glass-på-glass eller glass-på-metall (f.eks. skillevegger eller glassdører)

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |                |                  |         |
|-----------------|----------------|------------------|---------|
| • Bæremateriale | filled acrylic | • Total tykkelse | 1000 µm |
| • Klebetype     | Ren akryl      |                  |         |

### Klebekraft

- |                                     |         |
|-------------------------------------|---------|
| • Klebeevne på Stål (etter 3 dager) | 36 N/cm |
|-------------------------------------|---------|

### Additional Information

For more technical data please click on the following link to open our technical information sheet:

For latest information on this product please visit <http://l.tesa.com/?ip=07044>



# 7044

## Gray / White

### Product Information

### Additional Information

<https://www.tesa.com/ACX<sup>plus</sup>/TI-sheet>

The product is recommended for indoor usage. For permanent outdoor applications with load-bearing requirements, our product offer is tesa® ACX<sup>plus</sup> 707x series. To ensure the highest performance possible, our aim is to fully understand the application (including the substrates involved) to provide the best product recommendation.

Liner options:

- PV26: White paper liner – unbranded
- PV28: Blue film liner - unbranded
- PV48: White film liner - branded

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07044>