

# tesapack<sup>®</sup> Bio & Strong

## Product Information



BNR 58296

### Product Description

tesapack<sup>®</sup> BIO & STRONG is a more sustainable high tack tape. With strong adhesion for packages up to 20 kg and transparent material made from renewable raw materials, the tape is an impressive all-rounder.

### Product Features

- tesapack<sup>®</sup> BIO & STRONG packaging tape for more sustainable packaging
- More sustainable high tack tape made from renewable raw materials
- Made from 98% renewable raw materials
- Transparent adhesive tape
- Easy unrolling by hand or with a dispenser
- Strong adhesion for secure sealing of packages up to 20 kg
- The high proportion of renewable materials has been confirmed by the independent certification organisations DIN CERTCO (TÜV Rheinland) and TÜV Austria.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                     |                   |       |
|--------------------|---------------------|-------------------|-------|
| • Backing          | Poly lactide (PLA)  | • Total thickness | 50 µm |
| • Type of adhesive | water-based acrylic |                   |       |

### Properties/Performance Values

- |                          |                    |                       |                  |
|--------------------------|--------------------|-----------------------|------------------|
| • Tensile strength       | 31.2 N/cm          | • Low noise unwinding | no               |
| • Adhesive strength      | Very high adhesion | • Solvent free        | yes              |
| • Ageing resistance (UV) | no                 | • Suitable surfaces   | Cardboard, Paper |
| • Hand tearability       | no                 | • Tear resistance     | yes              |



# tesapack<sup>®</sup> Bio & Strong

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>