



# tesa<sup>®</sup> Professional

## Product Information



BNR 60020, 60021

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- Uten silikon Ja

### Egenskaper / ytelsesverdier

• Anbefalt avstand til sprøyting	30 cm	• Krever batterier	Nei
• Batterier inkl.	Nei	• Løsemiddelfri	Nei
• Bruksområde	Hjemme, Kontor	• Miljøvennlig emballasje	Nei
• Farlig materiale	Ja	• Passer for barn på 3 år	Nei
• Fjernes uten kleberester	Nei	• Temperaturbestandighet	Ja
• Fuktbestandighet	Ja	• Temperature resistance max.	60 °C
• Kan brukes om igjen	Nei	• Temperature resistance min.	-20 °C
• Kan vaskes	Nei	• UV-bestendig	Ja
• Kjemikaliebestandig	Ja	• Vannnett	Ja
• Klebekraft	Lett vedheft	• Velegnede overflater	Jevnt tre, Murstein, Akrylglas, Stein
• Komposterbart	Nei		

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>