



# tesa<sup>®</sup> PRO 74662 STRONG Duct Tape

## Product Information

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

• Bæremateriale	PE-film med PET filament	• Total tykkelse	215 µm
• Klebetype	Syntetisk gummi		

### Egenskaper / ytelsesverdier

• Bruddforlengelse	19 %	• Løsemiddelfri	Ja
• Bruddstyrke	40 N/cm	• Rette avrivningskanter	good
• Avrullningskraft n/cm	2 N/cm	• Rivebestandig	Ja
• Fjernes uten kleberester	Nei	• Slitstyrkebestandighet	good
• Hand tearability	very good	• UV-bestandig	Ja
• Kan skrives på	Nei	• Velegnede overflater	Jevnt tre, Fliser, De fleste plasttyper, Glass, Metall
• Klebeevne	very good		
• Lett å fjerne	Nei	• Vevstetthet	27 count per square inch
		• Water resistance	good

### Klebekraft

• Klebeevne på ru overflater	6.5 N/cm	• Klebeevne på Stål	8 N/cm
------------------------------	----------	---------------------	--------

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=74662>